



BUCKET (표준 SIZE) :  
CHAIN 3M~14M)기 적용

BUCKET (중 SIZE) :  
CHAIN 14M~28M)기 적용

SPECIFICATION

HOISTING LOAD	1.5 TON	
TESTING LOAD	1.875 TON	
LIFTING HEIGHT	Min. 3 M ~ Max 50 M	
HOISTING	SINGLE	SPEED 8.0 M/MIN MOTOR 2.5 Kw x 4 P
	DUAL	SPEED 8.0 / 4.0 M/MIN MOTOR 2.5/1.25 Kw x 4/8 P
FAST	SPEED 19.0 M/MIN MOTOR 0.4 Kw x 4 P	
	MIDDLE	SPEED 12.0 M/MIN MOTOR 0.27 Kw x 6 P
SLOW	SPEED 9.5 M/MIN MOTOR 0.2 Kw x 8 P	
	DUAL	SPEED 19 / 9.5 M/MIN MOTOR 0.4/0.2 Kw x 4/8 P
POWER SUPPLY	3Ø-220~575V-60Hz	
CONTROL VOLTAGE	1Ø -48, 110V -60Hz	
OPERATING METHOD	PUSH BUTTON TYPE	
LOAD CHAIN SPEC.	Ø8.0 x 24P x 1 FALL	
WIDTH OF BEAM	100~150 mm	
RADIUS OF BEAM	MIN. 1500 mm	
RATING	30 MIN.	
NET WEIGHT	APPROX Min.92KG~Max.144KG	

DIMENSIONS

구분	양정(LIFT)		
	3M~13M	14M~26M	26M~45M
기준	620	710	910
C			

NO.	DESCRIPTION	MAT'L	SIZE	Q'TY	REMARKS
800	TROLLEY ASSY			1	
700	ELEC. ASSY			1	
600	HOIST MOTOR ASSY			1	
500	BUCKET ASSY			1	
400	BOTTOM HOOK ASSY			1	
200	GEAR BOX ASSY			1	
100	CENTER FRAME ASSY			1	

DESIGNED	CHECKED	SCALE	DWG. NO.
REVISION	APPROVED	DATE	
정영환	김민	2013.05.10	SCT-1500

SCT-1500



1.5 TON MOTOR TROLLEY TYPE  
ELEC. CHAIN HOIST GENERAL ASSEMBLY

REV	DATE	REASON FOR REVISION	CHECKER BY	APP'D BY
△				