



Specification(Single Girder With Mono Rail Hoist) >>

MODEL	CAPACITY(ton)	MAX SPAN(m)	LIFT (m)	SPEED/MOTOR(m/min)/(kw)			APPROX.DIMENSIONS(mm)							TRAVELING WHEEL(mm∅)	TRAVELING WHEEL(kg/m1)							
				HOISTING	TRAVERSING	TRAVELING	H	A	B	C	D	E	F									
OHS	1	8	6 or 9 or 12 or 18 or 24	8/1.5 or 12/2.2	16/0.5 or 24/0.75	16/0.75 x2 (1/16) or 22/0.75 x2 (1/11.8)	815	1500	1100	900	60	300	600	∅160	15							
		2000						1600	950	650												
		2500						2100	1050	750												
		3200						2800	1150	850												
		3900						3500	1250	950												
OHS	2	8		6/1.5 or 10/3.7			16/0.5 or 24/0.75	16/0.75 x2 (1/16) or 22/0.75 x2 (1/11.8)	960	1500			1100	1000	60	300	700	∅200	22			
		2000								1600			1000	700								
		2600								2100			1120	820								
		3300								2800			1180	880								
		4000								3500			1300	1000								
OHS	3 (2.8)	8		4.5/2.8 or 9/5.5			16/0.5 or 24/0.75		16/0.75 x2 (1/16) or 22/0.75 x2 (1/11.8)	1115			1500	1100			900	60	300	700	∅160	15
		2000											1600	1000			700					
		2500											2100	1100			820					
		3000											2600	1160			880			∅200	22	
		3300											2800	1300			1000					
		4000	3500		1350	1050																
		OHS	5		8	4.2/2.2 or 5.6/5.5					16/0.5 or 24/0.75	16/0.75 x2 (1/16) or 22/0.75 x2 (1/11.8)	1325	1500			1100					1030
1750	1350			1030	730																	
2250	1750			1180	880		∅200			22												
2500	2000			1180	880																	
2700	2200			1300	1000																	
3000	2500			1300	1000																	
3050	3500			1620	1320																	
OHS	10 (7.5)	8	4.5/9 or 6/13	10/0.5 x0 or 16/0.75 x2	20/1.5 x2 (1/10) or 30/1.5 x2 (1/8)	1520	2050	1500		1150	60		300	850	∅250	30						
		2550					2000	1300		1000												
		3050					2500	1450	1150													
		3600					3000	1750	1450	∅315				30								
		4100					3500	1950	1650													