



Specification(Single Girder With Mono Rail Hoist)

| MODEL | CAPA-CITY(ton) | MAX SPAN(m) | LIFT (m) | SPEED/MOTOR(m/min)/(kw) | | | APPROX.DIMENSIONS(mm) | | | | | | TRAVELING WHEEL(mmø) | RUN WAY RAIL |
|-------|----------------|-------------|--------------------------|--------------------------|-------------------------|--|-----------------------|------|------|-----|-----|---|----------------------|---|
| | | | | HOISTING | TRAVERSING | TRAVELING | H | A | B | C | D | E | | |
| SCC | 0.5 | 6 | 6 | 8/1.5 or 12/2.2 | | | 705 | 1200 | 800 | 280 | 120 | | | |
| | | 9 | | | | | | 1600 | 1200 | | | | | |
| | | 12 | | | | | | 2000 | 1600 | | | | | |
| | | 15 | | | | | | 2400 | 2000 | | | | | |
| | | 18 | | | | | | 2800 | 2400 | | | | | |
| SCC | 1 | 6 | 6 | 8/1.5 or 12/2.2 | | | 815 | 1200 | 800 | 280 | 120 | 320 (100)/ 345 (125)/ 370 (150)/ 395 (175) | ø125 | I-BEAM 200×100×7t/ 20×125×7.5t/ 300×10×10t/ 450×175×11t/ 600×190×13t |
| | | 9 | | | | | | 1600 | 1200 | | | | | |
| | | 12 | | | | | | 2000 | 1600 | | | | | |
| | | 15 | | | | | | 2400 | 2000 | | | | | |
| | | 18 | | | | | | 2800 | 2400 | | | | | |
| SCC | 2 | 6 | 6 or 9 or 12 | 6/2.5 or 10/3.7 | 16/0.5 or 24/0.75 | 15/0.75/ 1/16 or 22/0.75/ 1/11.8 | 960 | 1200 | 800 | 350 | 150 | 361 (125)/ 386 (150)/ 411 (175) | ø160 | |
| | | 9 | | | | | | 1600 | 1200 | | | | | |
| | | 12 | | | | | | 2000 | 1600 | | | | | |
| | | 15 | | | | | | 2400 | 2000 | | | | | |
| | | 18 | | | | | | 2800 | 2400 | | | | | |
| SCC | 3 (7.5) | 6 | 6 or 9 or 12 | 4.5/2.8 or 9/5.5 | | | 1115 | 1200 | 800 | 350 | 150 | 395 (125)/ 420 (150)/ 445 (175) | ø180 | |
| | | 9 | | | | | | 1600 | 1200 | | | | | |
| | | 12 | | | | | | 2000 | 1600 | | | | | |
| | | 15 | | | | | | 2500 | 2000 | | | | | |
| | | 18 | | | | | | 2900 | 2400 | | | | | |
| SCC | 5 | 6 | 6 or 9 or 12 | 4.2/4.2 or 5.6/5.5 | | | 1520 | 1300 | 800 | 350 | 150 | 395 (125)/ 420 (150)/ 445 (175) | ø180 | |
| | | 9 | | | | | | 1700 | 1200 | | | | | |
| | | 12 | | | | | | 2100 | 1600 | | | | | |
| | | 15 | | | | | | 2500 | 2000 | | | | | |
| | | 18 | | | | | | 2900 | 2400 | | | | | |